

T-SERIES



Key Features & Benefits

- Choice of three trim ring diameters
- 2-wire power and dimming compatible with Imtra PowerLED PWM controller
- Bi-color dimming with single momentary switch (requires a 3rd wire)
- Secure screw-mounting ideal for weather-exposed locations

LED Colors

Single Color: Warm, Cool, Neutral

Bi-Color: Red/Warm, Blue/Warm, Red/Cool, Blue/Cool, Red/Neutral, Blue/Neutral



Specifications

	T-105	T-155	T-180
Beam angle (FWHM)	88°	87°	86°
Power consumption	4.7W		
Luminous flux (lm)*	189	197	206
Lifetime hours (70% light output)	50,000		
Halogen equivalency	25W		
Input voltage	10-40VDC		
Ingress protection (IP)	IP65		

* Luminous flux figures are for Warm White only. For other figures please refer to our website.

Finishes

Polished stainless steel	●	●	●
White	●	●	●
Optional custom finish (IP varies)		●	●




T-180



T-155



T-105



Dimensions

	T-105		T-155		T-180	
A Trim Ring Width	4.13"	105mm	6.10"	155mm	7.09"	180mm
B Recessed Depth	1.36"	35mm	1.13"	29mm	1.08"	27mm
C Cutout	3.03"	77mm	4.18"	106mm	5.10"	130mm
D Trim Ring Height	0.35"	9mm	0.35"	9mm	0.35"	9mm