

## POOL



### Key Features & Benefits

- Choice of three stainless steel twist-on bezel designs
- 2-wire power and dimming compatible with Imtra PowerLED PWM controller
- Bi-color dimming with single momentary switch (requires a 3<sup>rd</sup> wire)
- Integrated current-controlled drive circuitry
- Secure screw-mounting ideal for weather-exposed locations

### LED Colors

Single Color: Warm, Cool, Neutral

Bi-Color: Red/Warm, Blue/Warm, Red/Cool, Blue/Cool, Red/Neutral, Blue/Neutral




### Specifications

Beam angle (FWHM)	90°
Power consumption	4.7W
Luminous flux (lm)*	183
Lifetime hours (70% light output)	50,000
Halogen equivalency	25W
Input voltage	10-40VDC
Ingress protection (IP)	IP65

\* Luminous flux figures are for Warm White only. For other figures please refer to our website.

### Finishes

Polished stainless steel	●
Brushed stainless steel	●
White	●
PVD Gold	●
Optional custom finish (IP varies)	●



### Dimensions

<b>A</b>	Trim Ring Diameter	3.43"	87mm
<b>B</b>	Recessed Depth	1.05"	27mm
<b>C</b>	Cutout	2.40"	61mm
<b>D</b>	Trim Ring Height	0.29"	7.4mm

