

KPM350 Submersible Pump

OVERVIEW

The Predator 350 is the obvious choice for a heavy duty submersible pump. Designed for the demanding workboat market and chosen as the uncompromising solution for operators who want the most reliable product on the market. Meeting multiple standards, the tested KPM Bilge Predator was derived by market research based on customer feedback. Apart from outperforming any other electric pump on the market, the Bilge Predator is designed to be versatile with variants suitable for portable electric emergency pumps and black tank macerator applications and live well circulators.

KPM-MARINE
Innovating Safety at Sea



KPM350SW

FEATURES

- Includes aluminum mounting bracket with easy release for cleaning
- 24 volt running at 16 amps full pump load
- 9.8 ft. (3 meters) of marine grade cable (Longer as option)
- Run dry capability - 2 weeks (turned off test)
- IP68 and fully water proof to 15m depth
- Robust anti-corrosion hard anodized aluminum construction
- Stainless impeller system
- Fully repairable
- 1 year warranty
- 12g impact tested
- Warranty return rate 0.03% over 4000 units over 10 years
- Compact Diameter 114mm x 350mm long
- Spark resistant material and hermetically sealed
- 95% recyclable with no VOC's
- Quick glance red Indicator light to show running
- Wide range of approvals (DNV-GL, BV, Lloyds Register, and NK)
- 1.5"/38mm id pipe fitting

Not suitable for Layflat hose



PRODUCT DETAILS

Dimensions

Diameter	114mm/4.48"
Length	360mm/14.17"
Weight	7.5 kg/16.5lbs including bracket

Flow rate at 0m head

77 GPM (290 LPM)
4,620 GPH (17,400 LPH)

Flow rate at 3m head

66 GPM (250 LPM)
3,960 GPH (15,000 LPH)

Specifications

Voltage	24VDC
Amperage	12 Amp
Fuse	20 Amp
Motor Wattage	450W
Includes	3M (2x14AWG wire)

Options

Available in White, Emergency Signal Orange, Mil Spec Seafoam Green

Long reach variants available from 200-1000mm

Dual Level Float Switch Indicator (KPMFLOAT)

Non Return Valve (KPMNRV)